

MARINE RESIDUAL FUELS

Limit	Parameter	RMA 30	RMB 30	RMD 80	RME 180	RMF 180	RMG 380	RMH 380	RMK 380	RMH 380	RMK 700
Max.	Viscosity at 50°C (mm²/s)	30.0		80.0	180.0		380.0			700	
Max.	Density at 15°C (kg/m³)	960.0	975.0	980.0	991.0		991.1		1010.0	991.0	1010.0
Max.	Micro Carbon Residue (% m/m)	10		14	15	20	18	22		22	
Max.	Aluminium + Silicon (mg/kg)	80		80	80		80			80	
Max.	Ash (% m/m)	0.10		0.10	0.10	0.15	0.15	0.15		0.15	
Max.	Vanadium (mg/kg)	150		350	200	500	300	600		600	
Max.	Water (% V/V)	0.50		0.5	0.5		0.5			0.5	
Max.	Pour point in Summer (°C)	6	24	30	30		30			30	
Max.	Pour point in Winter (°C)	0	24	30	30		30			30	
Min.	Flash point (°C)	60		60	60		60			60	
Max.	Sulphur (% m/m)	3.5		4.00	4.50		4.50			4.50	
Max.	Total Sediment, Potential (% m/m)	0.10		0.10	0.10		0.10			0.10	
Max.	Zinc (mg/kg)	15									
Max.	Phosphorus (mg/kg)	15									
Max.	Calcium (mg/kg)	30									